


# N-PACK NPP



Type	Length L (mm)	Fixing Holes D (mm)
NPP 115	470	315
NPP 118	620	470
NPP 130	925	605
NPP 136	1230	800
NPP 158	1530	800
NPP 218	620	470
NPP 236	1230	800
NPP 258	1530	800

Luminaires for T8 fluorescent lamps for ceiling or trunking installation. Cover and attachments can be fitted quickly without tools, cutting installation and maintenance costs.

**Body and cover:** bonderised cold rolled 5/10 mm sheet steel with white epoxy-polyester powder paint finish. The cover is clip mounted to the body. **Lampholder:** polycarbonate, fitted to the body by a safety clip; complete with ring nuts as a further safety feature to guarantee IP40 and to prevent the lamp from fall; the "rotor" system enables continuous mount of luminaires.

**Starter:** positioned to the side of the body, allowing routine maintenance operations without need to remove lamp or accessories. Control gear and electric circuit: 230V 50Hz wired with heat-resistant (HT 90°C), fire-retardant cable in compliance with IEC 20-22/II, with explosion-proof capacitor and built-in discharge resistor in the HPF version, with power factor correction; terminal block with 2.5 mm<sup>2</sup> clamping screws.

**Cable entry:** using special hole in body through grommet or through knockouts at the end of the fittings.

Type	N° and Lamp Type	Version	Weight (kg)	Pack Qty. Box	Pallet	Product Code
<b>NPP</b>		Class: I 230V 50Hz	<b>IP 40</b>			
NPP 118 H	1 x F18 T8	HPF	1,30	1	234	7004225
NPP 136 H	1 x F36 T8	HPF	2,10	1	144	7004233
NPP 158 H	1 x F58 T8	HPF	2,70	1	144	7004238
NPP 218 H	2 x F18 T8	HPF	1,40	1	156	7004240
NPP 236 H	2 x F36 T8	HPF	3,10	1	96	7004244
NPP 258 H	2 x F58 T8	HPF	4,30	1	96	7004249

Single pack - Complete with /33 Cool White 4000K lamp.

NPP EB Electronic	Class: I	IP 40				
	230V 50Hz					
NPP 136 EB	1 x F36 T8	HPF	1,85	1	144	32421
NPP 158 EB	1 x F58 T8	HPF	2,20	1	144	33062
NPP 236 EB	2 x F36 T8	HPF	2,40	1	96	30066
NPP 258 EB	2 x F58 T8	HPF	3,10	1	96	32189

With electronic ballast - Without lamp.

Type	N° and Lamp Type	Version	Weight (kg)	Pack Qty. Box	Pallet	Product Code
<b>NPP/X</b>		Class: I 230V 50Hz	<b>IP 40</b>			
NPP/X 118 H	1 x F18 T8	HPF	1,30	4	324	7004226
NPP/X 136 H	1 x F36 T8	HPF	2,10	4	180	7004234
NPP/X 158 H	1 x F58 T8	HPF	2,70	4	180	7004239
NPP/X 218 H	2 x F18 T8	HPF	1,40	4	168	7004241
NPP/X 236 H	2 x F36 T8	HPF	3,10	4	112	7004245
NPP/X 258 H	2 x F58 T8	HPF	4,30	4	112	7004250

Fourpack - Without lamp.

NPP EES Emergency	Class: I	IP 40				
	230V 50Hz					
NPP 136 H EES	1 x F36 T8	HPF	2,55	1	144	7004232
NPP 158 H EES	1 x F58 T8	HPF	3,25	1	144	7004237
NPP 258 H EES*	2 x F58 T8	HPF	4,75	1	96	7004248

With emergency battery - (\*one lamp on emergency) - Without lamp.

Note the resistance to chemical agents in construction materials.  
• HPF = with power factor correction